

ECO 123-AIR Precision ambient thermometer with alarm

- modern and functional housing
- Quick and precise measurement
- Alarm function with buzzer
- 3-line display / overhead display at the push of a button
- Backlight
- Air temperature measurements with best possible precision
- Robust, long battery life
- Hold-function to freeze measured values
- Min/Max-function for minimum and maximum recorded measured values



DESCRIPTION

When developing the new ECO 123-AIR, the focus was deliberately on the essential functions of measurement technology - the sensor design combines a highly precise and reliable sensor and a protective function that provides a practical solution for adequate sensor protection and the best possible response speed.

Precision, speed and reliability, packaged in a compact and robust housing, make the device a reliable partner for professional users, Made in Germany.

The device is used in building management as well as in meteorology - whenever fast on-site detection / reference measurement is required.

The simple alarm function makes it easier to monitor the temperature "in parallel" while you can do other things at the same time.



ECO 123-AIR sensor detail

ECO 123-AIR Precision ambient thermometer with alarm

Display

Thanks to the backlight, the three-line LCD display offers ergonomic wide-angle visibility - by day and by night.

The HOLD function enables the display values to be frozen.

Power supply

2 powerful AA batteries, the energy-saving design and the configurable automatic switch-off function ensure long operation.

Configurable LCD backlight for further energy saving options.

TECHNICAL DATA

Measurement specifications

Input	fixed Pt1000 probe, protective tube Ø14x37 mm, with large air openings
Measuring range	Temperature -25.0 ... +70.0 °C
Accuracy (at nominal temperature)	Max. ±0.5 % of measured value ±0.5 °C
Response time	T ₉₀ at 1m/s air movement ca 15s

General specifications

Display	3-line with battery status indicator, Backlight, protected by shatterproof screen, overhead display at keypress
Power supply	2 x AA Alkaline batteries (included)
Power consumption	ca. 0.4 mA, ca .2 mA with backlight
Battery life	ca. 5000 h typ. continuous operation, without backlight
Automatic Power-Off	Yes, configurable by the user
Operating conditions	-20 to 50 °C; 0 to 85 % r.h. (non-condensing)
Storage temperature	-25...70 °C (without batteries)
Protection class	IP20
Dimensions	140 x 54 x 28 mm (H x W x D)
Weight	approx. 130 g
Housing	Impact resistant ABS, Polyester (front panel), sensor protection cap PVDF

SCOPE OF DELIVERY

- handheld device (with or without probe) according to IP 65 / 67
- 2x AA battery
- Manual

ECO 123-AIR Precision ambient thermometer with alarm

ORDERING CODES

ECO123-AIR-__	
Scope of supply	
	Device in carton box, batteries, manual
-GKK1000	Device in case GKK 1000, batteries, manual
-WPT2P	Device in case GKK 1000, factory calibration ISO-WPT-2P-10-25°C, batteries, manual

STANDARD-ARTICLES

ECO123-AIR	Precision ambient thermometer with alarm Device in carton box, batteries, manual	Art no. 487497
ECO123-AIR-WPT2P	Precision ambient thermometer with alarm Device in case GKK 1000, factory calibration ISO-WPT-2P-10-25°C, batteries, manual	Art no. 487513

ACCESSORIES

GCLIP1000	Metal belt clip self-adhesive	Art no. 475820
G1000-BASE	ECO-line combined table base / wall suspension	Art no. 481885
GKK1000	Carrying case	Art no. 611603

For further articles, please visit Senseca website.